



AC200180
Canopy extractor 200 series
Stainless steel and glass
Width 70 cm
Air extraction / Air recirculation

Can be integrated invisibly in upper cabinet
Energy-saving, low-noise fan
Rim extraction with flat and easy-to-clean glass underside
Dimmable, neutral white LED light for ideal illumination of the whole cooktop
Air extraction or air recirculation system

Output

Performance and noise level, output level 3/Intensive: Air output according to EN 61591. Sound power level according to EN 60704-3. Sound pressure level according to EN 60704-2-13. Odour reduction for air recirculation in accordance with EN 61591.

Air extraction: 575 / 775 m³/h. 65 / 72 dB (A) re 1 pW. 51 / 58 dB (A) re 20 µPa.

Air recirculation: 570 / 740 m³/h. 73 / 78 dB (A) re 1 pW. 59 / 64 dB (A) re 20 µPa.

Odour reduction air recirculation 93 %.

Features

3 electronically controlled power levels and 1 intensive mode.
Remote control is available as a special accessory.
Interval ventilation, 6 min.
Run-on function, 6 min.
Grease filter saturation indicator.
Metal grease filter, dishwasher-safe.
Glass filter cover.
Neutral white LED light (4000 K), dimmable.
Lamp output 2 x 1 W.
Illuminance 244 lx.
Fan technology with highly efficient, brushless DC motor (BLDC).

Consumption data

Energy consumption 46.6 kWh/year.
Sound level min. 42 dB / max. 65 dB normal mode.

Planning notes

Patented air recirculation module with activated charcoal filter can be installed in the upper cabinet. The activated carbon filter can be changed from the front by simply pulling out the filter drawer.

The door of the upper cabinet must be fully open in order to change the activated charcoal filter.

Can be integrated invisibly in upper cabinet.

Vario cooktops with intensive production of vapours like VR/VP should be placed in the middle beneath the hood (in this case air recirculation is not recommended).

Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).

Clearance above electric appliances min. 50 cm.

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Total connected load 272 W.
Connecting cable 1.0 m with plug.

Characteristics

Product name/family

Color chimney

Typology

Traditional

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

100

Required niche size for installation (HxWxD)

418mm x 676.0mm x 264mm

Height of the chimney (mm)

Height of product, without chimney (mm)

Minimum distance above an electric hob

500

Minimum distance above a gas hob

650

Net weight (kg)

10.734

Type of control

Electronic

Number of speed settings

Maximum output air extraction (m³/h)

575

Boost position output recirculating (m³/h)

740.0

Maximum output recirculating air (m³/h)

775

Boost position air extraction (m³/h)

775

Number of lights

2

Noise level (dB)

65

Diameter of air outlet (mm)

120 / 150

Grease filter material

Washable aluminium

EAN code

4242006257491

Consumption and connection features

Connection Rating (W)

272

Current (A)

3

Voltage (V)

220-240

Frequency (Hz)

50

Plug type

Gardy plug w/ earthing

Installation typology

Built-in

2020-04-15

Page 1

Color Variants

AC200180

Stainless steel and glass

Width 70 cm

Optional accessories

AA200510

Remote control for canopy extractor

AC200

AC200180
Canopy extractor 200 series
Stainless steel and glass
Width 70 cm
Air extraction / Air recirculation
2020-04-15
Page 2

