



**BOP251112**  
**Oven 200 series**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**left-hinged**

Flush installation  
 Pyrolytic system  
 13 heating methods, with core temperature probe and baking stone function  
 Automatic programs  
 TFT touch display  
 Panel-free appliance with surface control module  
 Electronic temperature control from 30 °C to 300 °C  
 Net volume 76 litres

**Heating methods**  
 Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

**Handling**  
 Rotary knob and TFT touch display operation.  
 Option to save individual recipes (incl. core temperature probe).  
 Personalisation of automatic programs. Information key with use indicators.  
 Side-opening door opens up to 110° angle.

**Features**  
 Three-point core temperature probe with automatic shut-off and estimation of cooking time.  
 Automatic programs.  
 Baking stone socket.  
 Actual temperature display.  
 Rapid heating.  
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
 60 W halogen light on the top.  
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.  
 Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.  
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

**Safety**  
 Thermally insulated door with quintuple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

**Cleaning**  
 Pyrolytic system.  
 Gaggenau enamel.  
 Heated catalyser to clean the oven air.

**Planning notes**  
 Door hinge not reversible.  
 The door panel surface of the appliance extends 21 mm from the furniture cavity.  
 The outer edge of the door handle extends 72 mm from the furniture cavity.  
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.  
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 110° door opening angle.

**Characteristics**

**Color / Material Front**  
**Built-in / Free-standing**  
 Built-in  
**Integrated Cleaning system**  
 Pyrolytic  
**Required niche size for installation (HxWxD)**  
 590-590 x 560-560 x 550  
**Dimensions of the product (mm)**  
 595 x 590 x 547  
**Dimensions of the packed product (HxWxD) (mm)**  
 760 x 710 x 650  
**Control Panel Material**  
**Door Material**  
 Glass  
**Net weight (kg)**  
 55.193  
**Usable volume of cavity (l)**  
 76  
**Cooking method**  
 Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat  
**First cavity material**  
**Temperature control**  
 electronic  
**Number of interior lights**  
 1  
**Approval certificates**  
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE  
**Length electrical supply cord (cm)**  
**EAN code**  
 4242006286286

**Consumption and connection features**  
**Number of cavities (2010/30/EC)**  
 1  
**Energy efficiency class (2010/30/EC)**  
 A  
**Energy consumption per cycle conventional (2010/30/EC)**  
 1.25  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
 0.83  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
 95.4  
**Energy efficiency index (2010/30/EC)**  
 95.4  
**Connection Rating (W)**  
 3700  
**Current (A)**  
 16  
**Voltage (V)**  
 220-240  
**Frequency (Hz)**  
 50  
**Plug type**  
 no plug  
**2020-09-06**  
**Page 1**

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.  
 To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.  
 The mains socket needs to be planned outside the built-in niche.  
 The LAN port can be found at the back on the upper right side.

**Connection**  
 Total connected load 3.7 KW.  
 Plan a connection cable.  
 Plan a LAN cable.  
 Please check the user manual for how to switch off the WiFi module.

**Color Variants**  
**BOP251112**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**BOP251102**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

**Optional accessories**  
**BA016105**  
**Pull-out system**  
**BA056115**  
**Heating element for baking stone and Gastronorm roaster.**  
**BA056133**  
**Baking stone.**  
**GN340230**

**Product Variants**  
**BOP250112**  
**Oven 200 series**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**

BOP251112  
Oven 200 series  
Full glass door in Gaggenau Metallic  
Width 60 cm  
left-hinged  
2020-09-06  
Page 2

