



Color Variants

BS471112

Optional accessories

BA010301

3-level telescopic rails

CLS10040

Cleaning cartridges, set of 4

GN340230

Product Variants

BS470112

Combi-steam oven 400 series

Stainless steel-backed full glass door

Width 60 cm

right-hinged

Controls at the top

BS474112

BS475112

Combi-steam oven 400 series

Stainless steel-backed full glass door

Width 60 cm

left-hinged

Controls at the bottom

Characteristics

Color / Material Front

Built-in / Free-standing

Built-in

Door opening

Lateral

Required niche size for installation (HxWxD)

450-450 x 560-560 x 550

Dimensions of the product (mm)

455 x 590 x 540

Dimensions of the packed product (HxWxD) (mm)

590 x 660 x 690

Control Panel Material

Door Material

Stainless steel behind glass

Net weight (kg)

47.573

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

175

EAN code

4242006277666

Consumption and connection features

Electrical connection rating (W)

Current (A)

16

Voltage (V)

220-240

Frequency (Hz)

50

Plug type

Gardy plug w/ earthing

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Number of cavities (2010/30/EC)

1

Usable volume (of cavity) - NEW (2010/30/EC)

50

Energy efficiency class (2010/30/EC)

A

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

0.72

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

94.7

2020-09-06

Page 1